20V N-CHANNEL ENHANCEMENT MODE MOSFET

SUMMARY

$V_{(BR)DSS}$=20V; $R_{DS(ON)}$= 0.1Ω; I_D=3.2A



SOT23-6

DESCRIPTION

This new generation of high density MOSFETs from Zetex utilise a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.

FEATURES

- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- SOT23-6 package



APPLICATIONS

- DC - DC Converters
- Power Management Functions
- Disconnect switches
- Motor control



Top View

ORDERING INFORMATION

DEVICE	REEL SIZE (inches)	TAPE WIDTH (mm)	QUANTITY PER REEL
ZXM62N02E6TA	7	8mm embossed	3000 units
ZXM62N02E6TC	13	8mm embossed	10000 units

DEVICE MARKING

- 2N02

ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V_{DSS}	20	V
Gate Source Voltage	V_{GS}	± 12	V
Continuous Drain Current (V_{GS}=4.5V; T_A=25°C)(b) (V_{GS}=4.5V; T_A=70°C)(b)	I_D	3.2 2.6	A
Pulsed Drain Current (c)	I_{DM}	18	A
Continuous Source Current (Body Diode) (b)	I_S	2.1	A
Pulsed Source Current (Body Diode)	I_{SM}	18	A
Power Dissipation at T_A=25°C (a) Linear Derating Factor	P_D	1.1 8.8	W mW/°C
Power Dissipation at T_A=25°C (b) Linear Derating Factor	P_D	1.7 13.6	W mW/°C

THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient (a)	$R_{\theta JA}$	113	°C/W
Junction to Ambient (b)	$R_{\theta JA}$	73	°C/W

NOTES

(a) For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions

(b) For a device surface mounted on FR4 PCB measured at t≤5 secs.

(c) Repetitive rating - pulse width limited by maximum junction temperature. Refer to Transient Thermal Impedance graph.

CHARACTERISTICS



Safe Operating Area



Derating Curve



Transient Thermal Impedance



Transient Thermal Impedance

ELECTRICAL CHARACTERISTICS (at T_{amb} = 25°C unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	20			V	I_D=250μA, V_{GS}=0V
Zero Gate Voltage Drain Current	I_{DSS}			1	μA	V_{DS}=20V, V_{GS}=0V
Gate-Body Leakage	I_{GSS}			100	nA	V_{GS}=± 12V, V_{DS}=0V
Gate-Source Threshold Voltage	$V_{GS(th)}$	0.7			V	I_D=250μA, V_{DS}= V_{GS}
Static Drain-Source On-State Resistance (1)	$R_{DS(on)}$			0.1 0.125	Ω Ω	V_{GS}=4.5V, I_D=2.2A V_{GS}=2.7V, I_D=1.1A
Forward Transconductance	g_{fs}	3.2			S	V_{DS}=10V,I_D=1.1A
DYNAMIC (3)						
Input Capacitance	C_{iss}		460		pF	V_{DS}=15 V, V_{GS}=0V, f=1MHz
Output Capacitance	C_{oss}		150		pF	
Reverse Transfer Capacitance	C_{rss}		50		pF	
SWITCHING(2) (3)						
Turn-On Delay Time	$t_{d(on)}$		4.0		ns	V_{DD}=10V, I_D=2.2A R_G=6.0Ω, R_D=4.4Ω (refer to test circuit)
Rise Time	t_r		10.4		ns	
Turn-Off Delay Time	$t_{d(off)}$		16.9		ns	
Fall Time	t_f		8.0		ns	
Total Gate Charge	Q_g			6.3	nC	V_{DS}=16V,V_{GS}=4.5V, I_D=2.2A (refer to test circuit)
Gate-Source Charge	Q_{gs}			1.5	nC	
Gate Drain Charge	Q_{gd}			2.5	nC	
SOURCE-DRAIN DIODE						
Diode Forward Voltage (1)	V_{SD}			0.95	V	T_j=25°C, I_S=2.2A, V_{GS}=0V
Reverse Recovery Time (3)	t_{rr}		17.5		ns	T_j=25°C, I_F=2.2A, di/dt= 100A/μs
Reverse Recovery Charge (3)	Q_{rr}		8.6		nC	

(1) Measured under pulsed conditions. Width=300μs. Duty cycle ≤2% .
(2) Switching characteristics are independent of operating junction temperature.
(3) For design aid only, not subject to production testing.

TYPICAL CHARACTERISTICS



Output Characteristics



Output Characteristics



Typical Transfer Characteristics



Normalised RDS(on) and VGS(th) v Temperature



On-Resistance v Drain Current



Source-Drain Diode Forward Voltage

TYPICAL CHARACTERISTICS



Capacitance v Drain-Source Voltage



Gate-Source Voltage v Gate Charge



Basic Gate Charge Waveform



Gate Charge Test Circuit



Switching Time Waveforms



Switching Time Test Circuit

ZXM62N02E6

PACKAGE DIMENSIONS



DIM	Millimetres		Inches	
	Min	Max	Min	Max
A	0.90	1.45	0.35	0.057
A1	0.00	0.15	0	0.006
A2	0.90	1.30	0.035	0.051
b	0.35	0.50	0.014	0.019
C	0.09	0.20	0.0035	0.008
D	2.80	3.00	0.110	0.118
E	2.60	3.00	0.102	0.118
E1	1.50	1.75	0.059	0.069
L	0.10	0.60	0.004	0.002

PAD LAYOUT DETAILS



Zetex plc.
Fields New Road, Chadderton, Oldham, OL9-8NP, United Kingdom.
Telephone: (44)161 622 4422 (Sales), (44)161 622 4444 (General Enquiries)
Fax: (44)161 622 4420

Zetex GmbH
Streitfeldstraße 19
D-81673 München
Germany
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49

Zetex Inc.
47 Mall Drive, Unit 4
Commack NY 11725
USA
Telephone: (516) 543-7100
Fax: (516) 864-7630

Zetex (Asia) Ltd.
3510 Metroplaza, Tower 2
Hing Fong Road,
Kwai Fong, Hong Kong
Telephone:(852) 26100 611
Fax: (852) 24250 494

These are supported by
agents and distributors in
major countries world-wide

Internet:http://www.zetex.com